The agile solution for dynamic floorcare performance







Get closer to the edge than ever before

Conquer every corner and every aisle – every time

Built to deliver high-performance floorcare without interfering in your daily business, the compact, highly maneuverable SC5000 is designed to succeed in the most challenging environments.

With a clear view of every cleaning path, and ergonomic controls for intuitive use with minimal training, your operator can focus on getting the job done quickly and effectively – while maintaining complete awareness of their surroundings.

By pairing easy operation with trusted Nilfisk performance, in a new form factor that's more space-efficient than ever, the SC5000 represents our commitment to smooth, easy cleaning from start to finish.

- 30 % more productivity per tank
- SmartKey included
- 140 L tank capacity
- 4.5 hours' runtime

- 63 dB operating sound level
- 8 km/h operating speed
- Scrub path (cm):
 - 81 (disc)
 - 86 (cylindrical)
 - 91 (cylindrical)

Easier than ever

All command functions are integrated into the steering wheel – including user-specific SmartKey and SupervisorKey configurations – so operators can adjust the SC5000's settings to match any job.

Servicing and maintenance information is provided via the large, digital HUD.





Quick and nimble

Its best-in-class turning radius makes the SC5000 adept at getting around any corner, and down every aisle, without getting in the way – even in high-traffic environments.



Turn the biggest challenges into small ones

Handle the most complex cleaning environments with confidence – in any industry

Warehousing & Logistics

In spaces that can be tremendously open or extremely narrow, the agile SC5000 leaves floors spotless and safe in less time – and doesn't disrupt your business.

Light industry

SmartFlow[™] technology allows the SC5000 to strike a perfect balance between performance and resourceefficiency – without compromising on safety or visual presentation.

Heavy industry

With total environmental visibility, and an optional protective canopy, the SC5000 ensures safety while upholding your standard of clean.

Technical specifications

| Description | Unit | SC5000 34D (860) | SC5000 32C | SC5000 36C |
|--|-------------------------|------------------|------------------|------------------|
| Reference number | | 56116005 | 56116004 | 56116003 |
| Scrub Deck Type | | Disc | Cylindrical | Cylindrical |
| Scrub Path | mm | 860 | 810 | 910 |
| Maximum Cleaning Productivity per Hour | m ² per hour | 7740 | 5500 | 8190 |
| Scrub Brush Size | mm | 430 - Qty 2 | 810 | 910 |
| Brush Motor Power | | 1HP (750 Watt) | .75HP (550 Watt) | .75HP (550 Watt) |
| Soluiton / Recovery Tank Capacity | L | 140 | 140 | 140 |
| Gradability Scrubbing | degree | 7 | 10 | 10 |
| Sound Level | dBA | 64 | 59 | 59 |
| Voltage | V | 36 | 36 | 36 |
| Brush Speed | RPM | 250 | 900 | 900 |

Nilfisk A/S Kornmarksvej 1 · DK-2605 Brøndby · Denmark Tel. +45 43 23 81 00 · Fax +45 43 43 77 00 mail.com@nilfisk.com www.nilfisk.com

